

An ACI Standard

Code Requirements for  
Environmental Engineering  
Concrete Structures  
(ACI 350-20) and  
Commentary (ACI 350R-20)

Reported by ACI Committee 350

ACI 350-20



American Concrete Institute  
*Always advancing*



## **Code Requirements for Environmental Engineering Concrete Structures (ACI 350-20) and Commentary (ACI 350R-20)**

Copyright by the American Concrete Institute, Farmington Hills, MI. All rights reserved. This material may not be reproduced or copied, in whole or part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. In spite of these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI via the errata website at <http://concrete.org/Publications/DocumentErrata.aspx>. Proper use of this document includes periodically checking for errata for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided “as is” without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations with regard to health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

Participation by governmental representatives in the work of the American Concrete Institute and in the development of Institute standards does not constitute governmental endorsement of ACI or the standards that it develops.

Order information: ACI documents are available in print, by download, through electronic subscription, or reprint and may be obtained by contacting ACI.

Most ACI standards and committee reports are gathered together in the annually revised the ACI Collection of Concrete Codes, Specifications, and Practices.

**American Concrete Institute**  
**38800 Country Club Drive**  
**Farmington Hills, MI 48331**  
**Phone: +1.248.848.3700**  
**Fax: +1.248.848.3701**

[www.concrete.org](http://www.concrete.org)

# Code Requirements for Environmental Engineering Concrete Structures (ACI 350-20) and Commentary (ACI 350R-20)

An ACI Standard

Reported by ACI Committee 350

M. Reza Kianoush, Chair

Jon B. Ardahl, Vice Chair

Andrew R. Minogue, Secretary

Iyad M. Alsamsam  
John W. Baker  
Kiran Chandran  
Chuen-Shiow Chen  
Steven R. Close  
Mark W. Cunningham  
Ronald R. Fiore\*  
Anthony J. Galterio

Carl A. Gentry  
Lisa G. Giroux  
Ahmed Hafez  
Kenneth Ryan Harvey  
Keith W. Jacobson  
Edwina S. Lui  
Daniel J. McCarthy  
Kevin H. Monroe

Khalid Motiwala  
Jerry Parnes  
Risto Protic  
Satish K. Sachdev  
William C. Sherman  
Manwendra Sinha  
Pericles C. Stivaros  
Shashiprakash Surali

Lawrence M. Tabat\*  
John M. Tehaney  
Miroslav Vajvoda  
William A. Wallace  
Jeffrey S. Ward

## Consulting Members

William H. Backous  
Patrick J. Creegan  
Robert E. Doyle  
Anthony L. Felder  
Charles S. Hanskat

Jerry A. Holland  
David G. Kittridge  
Dennis C. Kohl  
Nicholas A. Legatos  
Kyle S. Loyd

Carl H. Moon  
Lawrence G. Mrazek  
Javeed Munshi  
Terry Patzias  
Andrew R. Philip

Narayan M. Prachand  
David M. Rogowsky  
Lawrence J. Valentine

\*Deceased.

ACI Committee Reports, Guides, and Commentaries are intended for guidance in planning, designing, executing, and inspecting construction. This document is intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. The American Concrete Institute disclaims any and all responsibility for the stated principles. The Institute shall not be liable for any loss or damage arising therefrom.

Reference to this document shall not be made in contract documents. If items found in this document are desired by the Architect/Engineer to be a part of the contract documents, they shall be restated in mandatory language for incorporation by the Architect/Engineer.

ACI 350-20 supersedes 350-06, became effective November 16, 2020, and was published October 2021.

Copyright © 2021, American Concrete Institute.

All rights reserved including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by electronic or mechanical device, printed, written, or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permission in writing is obtained from the copyright proprietors.

### PREFACE

The “Code Requirements for Environmental Engineering Concrete Structures” (Code) portion of this document covers the structural design, materials selection, and construction of environmental engineering concrete structures. Such structures are used for conveying, storing, or treating water and wastewater, other liquids, and solid waste. The term “solid waste” as used in the Code encompasses the heterogeneous mass of disposed-of materials, as well as more homogeneous agricultural, industrial, and mineral wastes.

The Code also covers the evaluation of existing environmental engineering concrete structures.

Environmental engineering concrete structures are subject to uniquely different loadings and severe exposure conditions that require more restrictive serviceability requirements and may provide longer service lives than non-environmental structures.

Loadings include normal dead and live loads, earth pressure loads, hydrostatic and hydrodynamic loads, and vibrating equipment loads. Exposures include concentrated chemicals, alternate wetting and drying, high-velocity flowing liquids, and freezing and thawing of saturated concrete. Serviceability requirements include liquid-tightness, gas-tightness, and durability.

Proper design, materials, and construction of environmental engineering concrete structures are required to produce serviceable concrete that is dense, durable, nearly impermeable, and resistant to relevant chemicals, with limited deflections and cracking. This includes minimizing leakage and control over the infiltration of, or contamination to, the environment or groundwater.

The Code presents additional material as well as modified portions of the ACI 318-05, ACI 318-08, and ACI 318-11 building codes that are applicable to environmental engineering concrete structures.

The Commentary discusses some of the considerations of the committee in developing the ACI 350 Code, and its relationship with ACI 318. Emphasis is given to the explanation of provisions that may be unfamiliar to some users of the Code. References to much of the research data referred to in preparing the Code are given for those who wish to study certain requirements in greater detail.

The chapter and section numbering of the Code are followed throughout the Commentary.

Among the subjects covered are: drawings and specifications, inspections, materials, concrete quality, mixing and placing, forming, embedded pipes, joints, reinforcement details, analysis and design, strength and serviceability, flexural and axial loads, shear and torsion, development of reinforcement, slab systems, walls, footings, precast concrete, prestressed concrete, shell structures, folded plate members, provisions for seismic design, and an alternate design method in Appendix A.

The quality and testing of materials used in the construction are covered by reference to the appropriate standard specifications. Welding of reinforcement is covered by reference to the appropriate AWS standard. Criteria for liquid-tightness and gas-tightness testing may be found in ACI 350.1.

**Keywords:** chemical attack; coatings; concrete durability; concrete finishing (fresh concrete); concrete slabs, crack width and spacing; cracking (fracturing); environmental engineering; hydraulic structures; inspection; joints (junctions); joint sealers; liners; liquid; patching; permeability; pipe columns; pipes (tubes); prestressed concrete; prestressing steels; protective coatings; reservoirs; roofs; serviceability; sewerage; solid waste facilities; tanks (containers); temperature; torque; torsion; vibration; volume change; walls; wastewater treatment; water; water-cementitious materials ratio; water supply; water treatment.

## INTRODUCTION

The Code and Commentary includes excerpts from ACI 318 that are pertinent to ACI 350. The Commentary discusses some of the considerations of ACI Committee 350 in developing this Code. Emphasis is given to the explanation of provisions that may be unfamiliar to users of the standard.

This Commentary is not intended to provide a complete historical background concerning the development of the Code, nor is it intended to provide a detailed summary of the studies and research data reviewed by the committee in formulating the provisions of the Code. However, references to some of the research data are provided for those who wish to study the background material in depth.

As the name implies, “Code Requirements for Environmental Engineering Concrete Structures” may be used as part of a legally adopted Code and, as such, must differ in form and substance from documents that provide detailed specifications, recommended practice, complete design procedures, or design aids.

The Code is intended to cover environmental engineering concrete structures but is not intended to supersede ASTM standards for precast structures.

Requirements more stringent than Code provisions may be desirable for unusual structures. The Code and Commentary cannot replace sound engineering knowledge, experience, and judgment.

A code for design and construction states the minimum requirements necessary to provide for public health and safety. ACI 350 is based on this principle. For any structure, the owner or the structural designer may require the quality of materials and construction to be higher than the minimum requirements necessary to provide serviceability and to protect the public as stated in the Code. Lower standards, however, are not permitted.

ACI 350 has no legal status unless adopted by government bodies having the power to regulate building design and construction. Where the Code has been adopted, it cannot present background details or suggestions for carrying out its requirements or intent. It is the function of the Commentary to fill this need. Where the Code has not been adopted, it may serve as a reference to good practice.

The Code provides a means of establishing minimum standards for acceptance of design and construction by a legally appointed building official or designated representatives. The Code and Commentary are not intended for use in settling disputes between the owner, engineer, architect, contractor, or their agents, subcontractors, material suppliers, or testing agencies. Therefore, the Code cannot define the contractual responsibility of the involved parties. General references requiring compliance with ACI 350 in the job specifications should be avoided, as the contractor is rarely in the position of accepting responsibility for architectural and engineering design details. Generally, the drawings, specifications, and contract documents should contain all the necessary requirements to ensure compliance with the Code. In part, this can be accomplished by reference to specific code sections in

the job specifications. Other ACI publications, such as ACI 350.5, “Specifications for Environmental Concrete Structures,” are written specifically for use as part of the contract documents for construction.

ACI Committee 350 recognizes the desirability of standards of performance for individual parties involved in the contract documents. Available for this purpose are the certification programs of the American Concrete Institute, plant certification programs of the Precast/Prestressed Concrete Institute and the National Ready Mixed Concrete Association, and qualification standards of the American Society of Concrete Contractors. Also available are “Standard Specification for Agencies Engaged in Construction Inspection and/or Testing” (ASTM E329) and “Standard Practice for Laboratories Testing Concrete and Concrete Aggregates for Use in Construction and Criteria for Laboratory Evaluation” (ASTM C1077).

### **Design aids (general concrete design aids are listed in ACI 318-11):**

“Rectangular Concrete Tanks,” Portland Cement Association, Skokie, IL, 1998, 182 pp. (Presents data for design of rectangular tanks.)

“Circular Concrete Tanks Without Prestressing,” Portland Cement Association, Skokie, IL, 1993, 54 pp. (Presents design data for circular concrete tanks built in or on ground. Walls may be free or restrained at the top. Wall bases may be fixed, hinged, or have intermediate degrees of restraint. Various layouts for circular roofs are presented.)

*Concrete Manual*, U.S. Department of Interior, Bureau of Reclamation, eighth edition, 1981, 627 pp. (Presents technical information for the control of concrete construction, including linings for tunnels, impoundments, and canals.)

“Design of Liquid-Containing Concrete Structures for Earthquake Forces,” Portland Cement Association, Skokie, IL, 2002, 60 pp. (Presents design examples for designing for hydrodynamic forces.)

“Moments and Reactions for Rectangular Plates” Engineering Monograph No. 27, United States Department of the Interior, Bureau of Reclamation, 1990, 100 pp. (Presents design aids for rectangular plates.)

## GENERAL COMMENTARY

Environmental engineering concrete structures are subject to stringent service conditions and should be designed for extended service life expectancy and detailed with care. The quality of concrete is important, and rigorous quality control must be maintained during construction to obtain dense, durable concrete suitable for the expected service conditions.

Environmental engineering concrete structures for the containment, treatment, or transmission of liquid such as water and wastewater as well as solid waste disposal facilities, should be designed and constructed to be liquid-tight, and where required, gas-tight, with minimal leakage under normal service conditions.

The liquid-tightness and gas-tightness of a structure will be reasonably assured if:

- a) The concrete mixture is properly proportioned, mixed, placed, consolidated, finished, and cured.
- b) Crack widths and depths are minimized.
- c) Joints are properly spaced, sized, designed, water-stopped, and constructed.
- d) Adequate reinforcing steel is provided, properly detailed, fabricated, and placed.
- e) Impervious protective coatings or barriers are used where required.

Usually it is more economical and dependable to resist liquid or gas permeation through the use of quality concrete, proper design of joint details, and adequate reinforcement, rather than by means of an impervious protective barrier or coating. Liquid-tightness or gas-tightness can also be obtained by appropriate use of shrinkage-compensating concrete. However, the engineer must recognize and account for the limitations, characteristics, and properties of shrinkage-compensating concrete as described in ACI 223 and ACI 224.2R.

Reduced permeability of the concrete is obtained by lowering the water-cementitious materials ratio as low as possible, without sacrificing acceptable workability and consolidation. Permeability decreases dramatically with extended periods of moist curing. In some cases, surface treatments can be an alternative to moist curing. Reduced permeability of the concrete surface can be achieved through the use of smooth forms or by troweling.

Air entrainment increases consolidation, reduces segregation and bleeding, increases workability, and provides

resistance to the effect of freezing-and-thawing cycles. Other admixtures, such as water reducers, are useful, as they increase workability and improve consolidation while lowering the water-cementitious materials ratio ( $w/cm$ ), which can increase strength characteristics. Use of some supplementary cementitious materials can also provide similar benefits. In addition, supplementary cementitious materials can also reduce permeability, increase durability, and extend service life.

Joint design should also account for movement resulting from thermal dimensional changes, differential settlements, and shrinkage strains induced by placement sequencing. Joints that form a barrier to the passage of liquids and gases are required to include waterstops in complete, closed circuits. Proper rate of concrete placement operations, adequate consolidation, and proper curing are also essential to control of cracking in environmental engineering concrete structures. Additional information on cracking is contained in ACI 224R and ACI 224.2R.

The design of the entire environmental engineering concrete structure as well as all individual members should be in accordance with the Code, which has been adapted from ACI 318. When all relevant loading conditions are considered, the design should provide adequate safety and serviceability, with a service life significantly greater than the service life expected if these structures were designed following the provisions of ACI 318. Some components of the structure, such as jointing materials, have a shorter life expectancy and will require maintenance or replacement.

The size of elements and amount of reinforcement should be selected on the basis of the serviceability and stress limits to promote long service life.

## CONTENTS

**PREFACE, p. 2****INTRODUCTION, p. 3****GENERAL COMMENTARY, p. 3****CHAPTER 1—GENERAL REQUIREMENTS, p. 5**

- 1.1—Scope, p. 5
- 1.2—Contract documents, p. 10
- 1.3—Inspection, p. 12
- 1.4—Approval of special systems of design or construction, p. 14

**CHAPTER 2—NOTATION AND DEFINITIONS, p. 15**

- 2.1—Code notation, p. 15
- 2.2—Definitions, p. 34

**CHAPTER 3—MATERIALS, p. 45**

- 3.1—Tests of materials, p. 45
- 3.2—Cementitious materials, p. 45
- 3.3—Aggregates, p. 46
- 3.4—Water, p. 48
- 3.5—Steel reinforcement, p. 49
- 3.6—Joint accessories, p. 55
- 3.7—Fibers, p. 57
- 3.8—Admixtures, p. 58
- 3.9—Storage of materials, p. 60
- 3.10—Referenced standards, p. 60

**CHAPTER 4—DURABILITY REQUIREMENTS, p. 67**

- 4.1—General, p. 67
- 4.2—Exposure categories and classes, p. 70
- 4.4—Additional requirements for freezing-and-thawing exposures, p. 79
- 4.5—Additional requirements for sulfate exposures, p. 80
- 4.6—Additional requirements for alkali-aggregate reactions, p. 81
- 4.7—Additional requirements for corrosion protection of reinforcement and other metal embedments, p. 84
- 4.8—Additional requirements for protection against chemical attack, p. 85
- 4.9—Additional requirements for protection against erosion, p. 89
- 4.10—Protection systems, p. 90
- 4.11—Tightness testing of structures, p. 92
- 4.12—Joints, p. 92

**CHAPTER 5—CONCRETE QUALITY, MIXING, AND PLACING, p. 95**

- 5.1—General, p. 95
- 5.2—Selection of proportions, p. 96
- 5.3—Proportioning concrete on the basis of field experience or trial mixtures, or both, p. 97

5.4—Proportioning shotcrete on the basis of field experience or trial mixtures, or both, p. 102

5.5—Average compressive strength reduction for concrete, p. 106

5.6—Average compressive strength reduction for shotcrete, p. 107

5.7—Evaluation and acceptance of concrete and shotcrete, p. 107

5.8—Preparation of equipment and place of deposit, p. 113

5.9—Mixing, p. 114

5.10—Conveying concrete and wet-mix shotcrete, p. 115

5.11—Depositing of concrete, p. 115

5.12—Application of shotcrete, p. 116

5.13—Curing, p. 116

5.14—Cold weather requirements, p. 118

5.15—Hot weather requirements, p. 118

**CHAPTER 6—FORMWORK AND EMBEDMENTS, p. 119**

6.1—Design of formwork, p. 119

6.2—Removal of forms, shores, and reshoring, p. 119

6.3—Embedments in concrete and shotcrete, p. 121

**CHAPTER 7—JOINTS, p. 123**

7.1—Jointing, p. 123

7.2—Construction joints, p. 128

7.3—Crack-inducing joints, p. 129

7.4—Movement joints, p. 130

7.5—Joint accessories, p. 131

**CHAPTER 8—ANALYSIS AND DESIGN – GENERAL CONSIDERATIONS, p. 137**

8.1—Design methods, p. 137

8.2—Loading, p. 137

8.3—Methods of analysis, p. 138

8.4—Redistribution of moments in continuous flexural members, p. 139

8.5—Modulus of elasticity, p. 141

8.6—Lightweight concrete, p. 141

8.7—Stiffness, p. 142

8.8—Effective stiffness to determine lateral deflections, p. 142

8.9—Span length, p. 143

8.10—Columns, p. 144

8.11—Arrangement of live load, p. 144

8.12—T-beam construction, p. 145

8.13—Joist construction, p. 145

8.14—Separate floor finish, p. 146

**CHAPTER 9—STRENGTH AND SERVICEABILITY REQUIREMENTS, p. 147**

9.1—General, p. 147

9.2—Required strength, p. 147

9.3—Design strength, p. 152

9.4—Design strength for reinforcement, p. 156



9.5—Control of deflections, p. 156

**CHAPTER 10—FLEXURE AND AXIAL LOADS, p. 163**

- 10.1—Scope, p. 163
- 10.2—Design assumptions, p. 163
- 10.3—General principles and requirements, p. 165
- 10.4—Distance between lateral supports of flexural members, p. 167
- 10.5—Minimum reinforcement of flexural members, p. 168
- 10.6—Distribution of flexural reinforcement, p. 168
- 10.7—Deep beams, p. 172
- 10.8—Design dimensions for compression members, p. 173
- 10.9—Limits for reinforcement of compression members, p. 173
- 10.10—Slenderness effects in compression members, p. 175
- 10.11—Axially loaded members supporting slab system, p. 182
- 10.12—Transmission of column loads through floor system, p. 182
- 10.13—Composite compression members, p. 183
- 10.14—Bearing strength, p. 185

**CHAPTER 11—SHEAR AND TORSION, p. 187**

- 11.1—Shear strength, p. 187
- 11.2—Shear strength provided by concrete for nonprestressed members, p. 190
- 11.3—Shear strength provided by concrete for prestressed members, p. 192
- 11.4—Shear strength provided by shear reinforcement, p. 195
- 11.5—Design for torsion, p. 200
- 11.6—Shear-friction, p. 210
- 11.7—Deep beams, p. 214
- 11.8—Provisions for brackets and corbels, p. 214
- 11.9—Provisions for walls, p. 218
- 11.10—Transfer of moments to columns, p. 220
- 11.11—Provisions for slabs and footings, p. 220

**CHAPTER 12—REINFORCEMENT—DETAILS, DEVELOPMENT, AND SPLICES, p. 233**

- 12.1—Standard hooks, p. 233
- 12.2—Minimum bend diameters, p. 233
- 12.3—Bending, p. 234
- 12.4—Surface conditions of reinforcement, p. 234
- 12.5—Placing reinforcement, p. 235
- 12.6—Spacing limits for reinforcement, p. 236
- 12.7—Concrete protection for reinforcement, p. 237
- 12.8—Development, p. 242
- 12.9—Splices, p. 262
- 12.10—Lateral reinforcement, p. 270
- 12.11—Reinforcement details for columns, p. 274
- 12.12—Connections, p. 274
- 12.13—Shrinkage and temperature reinforcement, p. 275

12.14—Requirements for structural integrity, p. 282

**CHAPTER 13—EARTHQUAKE-RESISTANT STRUCTURES, p. 285**

- 13.1—General requirements, p. 285
- 13.2—Ordinary moment frames, p. 292
- 13.4—Intermediate precast structural walls, p. 298
- 13.5—Flexural members of special moment frames, p. 298
- 13.6—Special moment frame members subjected to bending and axial load, p. 305
- 13.7—Joints of special moment frames, p. 309
- 13.8—Special moment frames constructed using precast concrete, p. 312
- 13.9—Special structural walls and coupling beams, p. 314
- 13.10—Special structural walls constructed using precast concrete, p. 323
- 13.11—Structural diaphragms and trusses, p. 323
- 13.12—Foundations, p. 328
- 13.13—Members not designated as part of the seismic-force-resisting system, p. 330

**CHAPTER 14—TWO-WAY SLAB SYSTEMS, p. 333**

- 14.1—Scope, p. 333
- 14.2—General, p. 334
- 14.3—Slab reinforcement, p. 334
- 14.4—Openings in slab systems, p. 338
- 14.5—Design procedures, p. 339
- 14.6—Direct design method, p. 342
- 14.7—Equivalent frame method, p. 348

**CHAPTER 15—WALLS, p. 353**

- 15.1—Scope, p. 353
- 15.2—General, p. 353
- 15.3—Walls prestressed circumferentially by wrapping with high-strength steel wire or strand, p. 353
- 15.4—Minimum reinforcement, p. 356
- 15.5—Walls designed as compression members, p. 357
- 15.6—Empirical Design Method, p. 357
- 15.7—Minimum wall thickness, p. 359
- 15.8—Walls as grade beams, p. 359

**CHAPTER 16—FOOTINGS, p. 361**

- 16.1—Scope, p. 361
- 16.2—Loads and reactions, p. 361
- 16.3—Footings supporting circular or regular polygon-shaped columns or pedestals, p. 362
- 16.4—Moment in footings, p. 362
- 16.5—Shear in footings, p. 362
- 16.6—Development of reinforcement in footings, p. 364
- 16.7—Minimum footing depth, p. 364
- 16.8—Transfer of force at base of column, wall, or reinforced pedestal, p. 364
- 16.9—Sloped or stepped footings, p. 366
- 16.10—Combined footings and mats, p. 366



**CHAPTER 17—PRECAST CONCRETE, p. 369**

- 17.1—Scope, p. 369
- 17.2—General, p. 369
- 17.3—Distribution of forces among members, p. 370
- 17.4—Member design, p. 371
- 17.5—Structural integrity, p. 371
- 17.6—Connection and bearing design, p. 373
- 17.7—Items embedded after concrete placement, p. 375
- 17.8—Marking and identification, p. 375
- 17.9—Handling, p. 375
- 17.10—Strength evaluation of precast construction, p. 376

**CHAPTER 18—COMPOSITE CONCRETE FLEXURAL MEMBERS, p. 377**

- 18.1—Scope, p. 377
- 18.2—General, p. 377
- 18.3—Shoring, p. 378
- 18.4—Vertical shear strength, p. 378
- 18.5—Horizontal shear strength, p. 378
- 18.6—Ties for horizontal shear, p. 379

**CHAPTER 19—PRESTRESSED CONCRETE, p. 381**

- 19.1—Scope, p. 381
- 19.2—General, p. 382
- 19.3—Design assumptions, p. 383
- 19.4—Serviceability requirements—flexural members, p. 385
- 19.5—Permissible stresses in prestressing steel, p. 388
- 19.6—Loss of prestress, p. 388
- 19.7—Flexural strength, p. 390
- 19.8—Limits for reinforcement of flexural members, p. 391
- 19.9—Minimum bonded reinforcement, p. 392
- 19.10—Statically indeterminate structures, p. 394
- 19.11—Compression members—combined flexure and axial loads, p. 395
- 19.12—Slab systems, p. 397
- 19.13—Post-tensioned tendon anchorage zones, p. 399
- 19.14—Design of anchorage zones for monostrand or single 5/8 in. diameter bar tendons, p. 404
- 19.15—Design of anchorage zones for multistrand tendons, p. 405
- 19.16—Corrosion protection for unbonded single-strand prestressing tendons, p. 406
- 19.17—Post-tensioning ducts, p. 408
- 19.18—Grout for bonded tendons, p. 408
- 19.19—Protection for prestressing steel, p. 410
- 19.20—Application and measurement of prestressing force, p. 410
- 19.21—Post-tensioning anchorages and couplers, p. 411
- 19.22—External post-tensioning, p. 412

**CHAPTER 20—SHELLS AND FOLDED PLATE MEMBERS, p. 413**

- 20.1—Scope and definitions, p. 413

- 20.2—Analysis and design, p. 415
- 20.3—Design strength of materials, p. 420
- 20.4—Shell reinforcement, p. 420
- 20.5—Construction, p. 422

**CHAPTER 21—LIQUID-CONTAINING GROUND-SUPPORTED SLABS, p. 423**

- 21.1—Scope, p. 423
- 21.2—Slab support, p. 424
- 21.3—Slab thickness, p. 425
- 21.4—Reinforcement, p. 426
- 21.5—Joints, p. 426
- 21.6—Hydrostatic uplift, p. 427
- 21.7—Curing, p. 427

**CHAPTER 22—STRENGTH EVALUATION AND CONDITION ASSESSMENT OF STRUCTURES, p. 429**

- 22.1—General, p. 429
- 22.2—Determination of required dimensions and material properties, p. 431
- 22.3—Condition survey of structures, p. 432
- 22.4—Field and laboratory testing, p. 433
- 22.5—Tightness testing, p. 434
- 22.6—Evaluation report, p. 434
- 22.7—Load testing, p. 435

**APPENDIX A—ALTERNATE DESIGN METHOD, p. 437**

- A.1—Scope, p. 437
- A.2—General, p. 438
- A.3—Allowable stresses at service loads, p. 438
- A.4—Development and splices of reinforcement, p. 440
- A.5—Flexure, p. 440
- A.6—Compression members with or without flexure, p. 441
- A.7—Shear and torsion, p. 441

**APPENDIX B—STRUT-AND-TIE MODELS, p. 447**

- B.1—Definitions, p. 447
- B.2—Strut-and-tie model design procedure, p. 453
- B.3—Strength of struts, p. 455
- B.4—Strength of ties, p. 458
- B.5—Strength of nodal zones, p. 460

**APPENDIX C—ALTERNATIVE PROVISIONS FOR REINFORCED AND PRESTRESSED CONCRETE FLEXURAL AND COMPRESSION MEMBERS, p. 463****APPENDIX D—ALTERNATIVE LOAD FACTORS, STRENGTH REDUCTION FACTORS, AND DISTRIBUTION OF FLEXURAL REINFORCEMENT, p. 471**

**APPENDIX E—ANCHORING TO CONCRETE, p. 479**

E.1—Definitions, p. 479

E.2—Scope, p. 483

E.3—General requirements, p. 484

E.4—General requirements for strength of anchors, p. 491

E.5—Design requirements for tensile loading, p. 497

E.6—Design requirements for shear loading, p. 509

E.7—Interaction of tensile and shear forces, p. 519

E.8—Required edge distances, spacings, and thicknesses to preclude splitting failure, p. 519

E.9—Installation and inspection of anchors, p. 521

**COMMENTARY REFERENCES, p. 527**



## CODE

CHAPTER 1—GENERAL  
REQUIREMENTS

## 1.1—Scope

**1.1.1** Except for primary containment of hazardous materials, this Code, where adopted under the requirements of the legally adopted building code, provides minimum requirements for the design and construction of reinforced concrete elements of environmental engineering concrete structures. In areas without a legally adopted building code, this Code defines minimum acceptable standards for materials, design, and construction practice. This Code also covers the strength

## COMMENTARY

CHAPTER R1—GENERAL  
REQUIREMENTS

## R1.1—Scope

The American Concrete Institute “**Code Requirements for Environmental Engineering Concrete Structures (ACI 350-20)**,” hereinafter referred to as this Code, provides minimum requirements for environmental engineering concrete design and construction practices.

The 2020 edition of this Code revised the previous code, ACI 350-06. This Code includes in one document the requirements for all reinforced concrete used for environmental engineering structures. This covers the spectrum of concrete containing nonprestressed reinforcement, prestressing steel, or composite steel shapes, pipe, or tubing.

Prestressed concrete is included under the definition of reinforced concrete. Provisions of this Code apply to prestressed concrete except those that are specifically stated to apply to nonprestressed concrete.

Chapter 13 of this Code contains provisions for design and detailing of earthquake-resistant structures. Refer to 1.1.9.

Appendix A of this Code contains provisions for an alternate method of design for nonprestressed reinforced concrete members using service loads (without load factors) and permissible service load stresses. The strength design method of this Code is intended to give design results similar to the Alternate Design Method.

Appendix B of this Code contains provisions for the design of regions near geometrical discontinuities, or abrupt changes in loadings.

Appendix C of this Code contains provisions for reinforcement limits based on  $0.75\rho_b$ , determination of the strength reduction factor  $\phi$ , and moment redistribution that have been in the ACI 318 codes for many years, including ACI 318-99. The provisions are applicable to reinforced and prestressed concrete members. When used, the provisions of Appendix C are to be used in their entirety.

Appendix D of this Code permits the use of load, environmental durability, strength reduction factors, and flexural reinforcement distribution provisions similar to those in Chapters 9 and 10 of ACI 350-01. Designs made using the provisions of Appendix D are equally acceptable as those based on the body of this Code, provided the provisions of Appendix D are used in their entirety.

Appendix E of this Code contains provisions for anchoring to concrete.

**R1.1.1** A hazardous material may be defined as a liquid, solid, gas, or sludge waste that contains properties that are dangerous or potentially harmful to human health or the environment. The Environmental Protection Agency (EPA) listed wastes are organized into three categories under the Resource Conservation and Recovery Act (RCRA): source-specific wastes, generic wastes, and commercial chemical products. Source-specific wastes include sludges and waste-

## CODE

evaluation and condition assessment of environmental engineering concrete structures.

In this Code, the term “concrete” shall also include shotcrete except where specifically indicated otherwise.

The specified concrete compressive strength shall not be less than 4000 psi. No maximum specified compressive strength shall apply unless restricted by a specific Code provision.

**1.1.1.1** Environmental engineering concrete structures are defined as concrete structures intended for conveying, storing, or treating water, wastewater, or other liquids and non-hazardous materials such as solid waste, and for secondary containment of hazardous liquids. For ancillary structures for which liquid-tightness, gas-tightness, or enhanced durability are essential, design considerations shall also conform to requirements of environmental engineering concrete structures.

**1.1.2** Precast concrete environmental structures designed and constructed in accordance with ASTM standards are not covered in this Code.

**1.1.3** This Code supplements the general building code and shall govern in all matters pertaining to design and construction of reinforced concrete elements of environmental engineering concrete structures, except wherever this Code is in conflict with requirements in legally adopted codes addressing environmental engineering concrete structures.

## COMMENTARY

waters from treatment and production processes in specific industries such as petroleum refining and wood preserving. The list of generic wastes includes wastes from common manufacturing and industrial processes such as solvents used in degreasing operations. The third list contains specific chemical products such as benzene, creosote, mercury, and various pesticides.

Shotcrete is pneumatically placed whereas other types of concrete are typically placed by gravity or pumped.

Below-grade structures, such as pump stations and pipe galleries, which are part of treatment facilities and which may be exposed to external groundwater pressures, generally are designed as environmental engineering concrete structures. Above-grade building structures that are not directly exposed to liquids, solid wastes, corrosive chemicals, corrosive gases, or high humidity associated with treatment facilities generally may be designed in accordance with the general building code or applicable industry standards. Nevertheless, consideration of corrosive effects on such structures may still be advisable.

**R1.1.1.1** Environmental engineering concrete structures include but are not limited to tanks, reservoirs, clarifiers, separators, lagoon liners, and secondary containment structures. Also included are hydraulic structures associated with flood control and water supply projects such as stilling basins, channels, portions of power houses, spillway piers, spray walls, training walls, flood walls, intake and outlet structures, flood control tunnels and shafts, energy-dissipating structures such as impact basins, lock walls, guide and guard walls, canal linings, and reinforced sections of concrete gravity dams.

**R1.1.2** Although precast environmental concrete structures designed and constructed in accordance with ASTM standards are not included in the scope of this Code, the licensed design professional should evaluate whether additional requirements may be necessary to minimize deterioration and to achieve the desired durability and service life of the structure. For example, ASTM C478 allows a maximum  $w/cm$  of 0.53 and the standard has no criteria that will permit addressing service conditions where the concrete may be exposed to freezing and thawing, harmful chemicals and gases, or harmful sulfates, all of which could accelerate deterioration and reduce durability of the structure and the expected service life.

**R1.1.3** The American Concrete Institute recommends that this Code be adopted in its entirety; however, it is recognized that when this Code is made a part of a legally adopted general building code, that general building code may modify some provisions of this Code.

## CODE

**1.1.4** This Code shall apply in all matters pertaining to design, construction, and material properties wherever this Code is in conflict with requirements contained in other standards referenced in this Code.

**1.1.5** The provisions of this Code shall govern for tanks, reservoirs, and other reinforced concrete elements of environmental engineering concrete structures. For special structures such as arches, bins and silos, blast-resistant structures, and chimneys, provisions of this Code shall govern where applicable. When an environmental concrete structure may be considered a building structure then it shall be designed to the requirements of this Code.

## COMMENTARY

**R1.1.5** Environmental engineering projects can contain several types of structures. For example, a treatment plant can contain environmental engineering concrete structures such as tanks and reservoirs, as well as an administration building. The ACI 350 Code would apply to the environmental structures, while ACI 318 could apply to the administration building. Also, the following ACI publications could apply to other structures.

“**Code Requirements for Reinforced Concrete Chimneys (ACI 307-08) and Commentary**” by ACI Committee 307. This standard prescribes material, construction, and design requirements for circular cast-in-place reinforced chimneys. It sets forth minimum loadings for the design of reinforced concrete chimneys and contains methods for determining the stresses in the concrete and reinforcement required as a result of these loadings.

“**Design Specification for Concrete Silos and Stacking Tubes for Storing Granular Materials (ACI 313-16) and Commentary**” reported by ACI Committee 313. This specification provides material, design, and construction requirements for reinforced concrete bins, silos, and bunkers and stave silos for storing granular materials. It includes recommended design and construction criteria based on experimental and analytical studies plus worldwide experience in silo design and construction.

Bins, silos, and bunkers are special structures, posing special problems not encountered in normal building design. While ACI 313 refers to “**Building Code Requirements for Structural Concrete (ACI 318)**” for many applicable requirements, it provides supplemental detail requirements and ways of considering the unique problems of static and dynamic loading of silo structures. Much of the criteria are empirical, but this specification does not preclude the use of more sophisticated methods that give equivalent or better safety and reliability.

ACI 313 sets forth recommended loadings and methods for determining the stresses in the concrete and reinforcement resulting from these loadings. Methods are recommended for determining the thermal effects resulting from stored material and for determining crack width in concrete walls due to pressure exerted by the stored material. Appendixes provide recommended minimum values of overpressure and impact factors.

“**Code Requirements for Nuclear Safety-Related Concrete Structures (ACI 349-06) and Commentary**” reported by ACI Committee 349. This standard provides minimum requirements for design and construction of concrete structures that form part of a nuclear power plant and that have nuclear safety-related functions. This stan-