

IN-LB

Inch-Pound Units

SI

International System of Units

Corrosion and Repair of Grouted Post-Tensioning Tendon Systems—Report

Reported by Joint ACI-ASCE Committee 423

ACI PRC-423.8-21



American Concrete Institute
Always advancing



Corrosion and Repair of Grouted Post-Tensioning Tendon Systems—Report

Copyright by the American Concrete Institute, Farmington Hills, MI. All rights reserved. This material may not be reproduced or copied, in whole or part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. In spite of these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI via the errata website at <http://concrete.org/Publications/DocumentErrata.aspx>. Proper use of this document includes periodically checking for errata for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided “as is” without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations with regard to health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

Participation by governmental representatives in the work of the American Concrete Institute and in the development of Institute standards does not constitute governmental endorsement of ACI or the standards that it develops.

Order information: ACI documents are available in print, by download, through electronic subscription, or reprint and may be obtained by contacting ACI.

Most ACI standards and committee reports are gathered together in the annually revised the ACI Collection of Concrete Codes, Specifications, and Practices.

American Concrete Institute
38800 Country Club Drive
Farmington Hills, MI 48331
Phone: +1.248.848.3700
Fax: +1.248.848.3701

www.concrete.org

Corrosion and Repair of Grouted Post-Tensioning Tendon Systems—Report

Reported by Joint ACI-ASCE Committee 423

Jeffery S. Volz, Chair

Amy M. Reineke Trygstad, Secretary

Theresa M. Ahlborn
Rashid Ahmed
Robert W. Barnes
Florian G. Barth
Asit N. Baxi
Roger J. Becker
Jared E. Brewe
Charles W. Dolan
James P. Donnelly

Martin J. Fradua
William L. Gamble
Harry A. Gleich
Pawan R. Gupta
William M. Hale
Trey Hamilton*
Carol Hayek*
Mohammad Iqbal
Thomas Kang

Donald P. Kline†
Larry B. Krauser
Jason J. Krohn
Thomas F. Mathews
Daniel J. McCarthy
Theodore L. Neff*
Sami H. Rizkalla
Carin L. Roberts-Wollmann
Brandon Ross

Bruce W. Russell
Thomas C. Schaeffer
Andrea J. Schokker*
Larbi M. Sennour
Edith G. Smith
Richard W. Stone
Miroslav Vejvoda*
Zuming Xia*

*Subcommittee members.

†Chair of subcommittee responsible for preparation of report.

Consulting Members

Kenneth B. Bondy
Robert N. Bruce Jr.
Chunsheng “Steve” Cai

Steven R. Close
Henry J. Cronin Jr.
Ward N. Marianos Jr.

Hani Melhem
Antoine E. Naaman
Thomas E. Nehil

H. Carl Walker
Paul Zia

This report provides general information regarding the evaluation of corrosion damage in structures reinforced with grouted multi-strand and bar tendons. A review of current practice is included along with the historical background. Specific potential problem areas for grouted tendons are discussed for each critical part of the tendon. Current methods for evaluating corrosion damage and typical repair schemes are included.

Keywords: anchorage; bonded; corrosion; duct; durability; grout; post-tensioning; prestressed; repair; strand; tendon.

ACI Committee Reports and Guides are intended for guidance in planning, designing, executing, and inspecting construction. This document is intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. The American Concrete Institute disclaims any and all responsibility for the stated principles. The Institute shall not be liable for any loss or damage arising therefrom.

Reference to this document shall not be made in contract documents. If items found in this document are desired by the Architect/Engineer to be a part of the contract documents, they shall be restated in mandatory language for incorporation by the Architect/Engineer.

CONTENTS

CHAPTER 1—INTRODUCTION, p. 2

- 1.1—Introduction, p. 2
- 1.2—Scope, p. 2
- 1.3—Limitations, p. 2

CHAPTER 2—DEFINITIONS, p. 3

CHAPTER 3—REVIEW OF CURRENT PRACTICE, p. 3

- 3.1—General, p. 3
- 3.2—Grouting requirements, p. 3
- 3.3—Tendon protection requirements, p. 4

CHAPTER 4—GROUTED TENDONS, p. 5

- 4.1—Evolution of grouted tendons, p. 5
- 4.2—Types of grouted tendons, p. 5
- 4.3—Potential problem areas, p. 5

ACI PRC-423.8-21 supersedes ACI 423.8R-10, was adopted July 19, 2021, and was published November 2021.

Copyright © 2021, American Concrete Institute.

All rights reserved including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by electronic or mechanical device, printed, written, or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permission in writing is obtained from the copyright proprietors.

- 4.4—Duct, p. 7
- 4.5—Grout, p. 8
- 4.6—Strand and bar, p. 9
- 4.7—Anchorage hardware and protection, p. 9

CHAPTER 5—EVALUATING CORROSION DAMAGE, p. 9

- 5.1—General, p. 9
- 5.2—Monitoring, p. 10
- 5.3—Nondestructive methods, p. 10
- 5.4—Exploratory methods, p. 11

CHAPTER 6—REPAIR SCHEMES AND METHODS, p. 11

- 6.1—General, p. 11
- 6.2—Grouting of voids, p. 11
- 6.3—Repair of tendons with soft grout, p. 11
- 6.4—Tendon repair and strengthening, p. 11
- 6.5—Other repair and protection strategies, p. 12

CHAPTER 7—REFERENCES, p. 12

- Authored documents, p. 12

CHAPTER 1—INTRODUCTION

1.1—Introduction

The use of grouted high-strength wire, strand, and bar post-tensioning tendons as a viable construction technique began in North America in the 1950s ([Post-Tensioning Institute 2006](#)). Components of the standard system have changed significantly from shimmed button-head wire-type systems to bundles of seven-wire strand systems with wedges. Post-tensioning bars may also be used in grouted systems, although they have not changed significantly since their first introduction. The latest generation of post-tensioning systems include multiple layers of corrosion protection due to an increased awareness of the susceptibility of earlier systems to corrosion and the importance of a durable system.

Grout material is used in post-tensioning tendons to fill the voids in the ducts, to provide bond between the tendons and the structural element, and to provide corrosion protection for the tendons. Historically, grout consisted of a standard mixture of water and portland cement; sometimes, however, chemical admixtures were included to increase pumpability, to introduce expansion in an attempt to counteract settlement and voids, or to reduce bleeding. In the late 1990s, the discovery of tendon corrosion in several post-tensioned bridges in Florida ([Corven Engineering, Inc. 2001](#)) prompted a change in grouting materials, including the introduction of prepackaged grout formulations containing anti-bleed admixtures. Past performance of grouted post-tensioning systems is covered in more detail in [4.1](#).

The discovery of corrosion problems has also led to the development of various methods for the evaluation and repair of corrosion damage to grouted tendon systems ([Hurlebaus et al. 2016](#)). Over the past two decades, many bridges have undergone evaluation and repairs, if required ([Schokker and Berg 2012](#); [Sprinkel and Balakumaran 2017](#)).

Evaluation methods vary; however, most include nondestructive methods as well as exploratory evaluation for detection of voids, water, or soft grout within the ducts and corrosion of the prestressing steel. Repairs typically consist of removal of water and soft grout followed by filling the voided space within the ducts with grout. If a tendon has lost significant cross section due to corrosion, the tendon may need to be replaced. [Chapters 5](#) and [6](#) cover evaluation and repair methods in greater detail.

1.2—Scope

This report includes a review and summary of the following:

- (a) Guide specifications and training as applied to grouted post-tensioning tendons
- (b) Quality control during construction
- (c) Potential problem areas in grouted systems
- (d) Durability enhancements for each component of the tendon
- (e) Evaluation and mitigation of corrosion problems
- (f) Repair methods for grouted systems

This report is intended to provide general information on the corrosion and repair of grouted multistrand and bar tendon systems. The information is intended to represent the state of knowledge of the committee in the areas of corrosion prevention in grouted tendons, as well as evaluation and repair. It is not intended as a standard or recommended practice. A strong background in durability of grouted post-tensioning systems, including practical experience and training, is recommended before designing, constructing, evaluating, or repairing these structures.

This report focuses on the unique materials and hardware associated with grouted post-tensioning tendons with a discussion of efforts within the industry to improve durability. This report also provides recent practice with regard to evaluation and repair of grouted post-tensioning systems. General corrosion theory for metals in structural concrete systems is not within the scope of this report. Information on corrosion theory and mechanisms can be found in [ACI 222R](#) and [ACI 222.2R](#). Information on inspection and evaluation of unbonded single-strand post-tensioning systems can be found in [PTI DC80.3/ICRI 320.6](#).

1.3—Limitations

This report presents a summary of the typical corrosion-related problems that may occur in grouted post-tensioning systems and includes guidelines for evaluation and repair. The material is general in nature and may not apply to every situation. Due to the uniqueness of each post-tensioned structure, engineering judgment should be used to determine the appropriate action based on experience and the general guidance provided in this document.

This report is not intended to be included as part of a specification document for materials, evaluations, or repairs. Evaluation of grouted post-tensioning tendons is a difficult undertaking, and no single method can be used to fully describe the damage or life expectancy of a tendon. Due to the many changes in materials and equipment since the