

Construction of Concrete Shells Using Inflated Forms

Reported by Joint ACI-ASCE Committee 334

David B. South
Chair

John F. Abel
David P. Billington
Arthur J. Boyt, Jr.
James L. Byrne
John V. Christiansen
Matthew S. Church

Frederick L. Crandall
Phillip L. Gould
Takashi Hara
Michael D. Hunter
Mark A. Ketchum
Samaan G. Ladkany

Luis F. Meyer
John C. Miller
Thomas E. Nelson, Jr.
John K. Parsons
Dale A. Pearcey
Ryan E. Poole

William C. Schnobrich
Barry South
Jason P. South
Arnold Wilson
L. Brent Wright

This report provides information on the construction of structural concrete shells using an inflated form. Major facets of the construction process are covered, including foundations, inflation, monitoring, and backup systems. Other aspects, such as the geometric variations of inflated forms, thickness of polyurethane foam, and mixture proportions for shotcrete, are also considered.

Keywords: dome; fabric; inflation; polyurethane foam; reinforcement; shotcrete; thin shell.

CONTENTS

Chapter 1—General, p. 334.3R-2

- 1.1—Introduction
- 1.2—Scope
- 1.3—History
- 1.4—Methods
- 1.5—Definitions
- 1.6—Preconstruction
- 1.7—Work schedule

Chapter 2—Foundations, p. 334.3R-4

- 2.1—General
- 2.2—Concrete

- 2.3—Soil conditions
- 2.4—Reinforcement material
- 2.5—Placement of reinforcement
- 2.6—Placement of anchors
- 2.7—Concrete placement
- 2.8—Foundation dowels
- 2.9—Uplift prevention

Chapter 3—Inflated forms, p. 334.3R-6

- 3.1—General
- 3.2—Inflated form material and manufacturing
- 3.3—Field layout
- 3.4—Form protection
- 3.5—Initial stretching
- 3.6—Inflation
- 3.7—Construction tolerances
- 3.8—Air pressure maintenance
- 3.9—Collapse prevention
- 3.10—Miscellaneous connections
- 3.11—Fabric form repair
- 3.12—Polyurethane foam (when used)
- 3.13—Preparation
- 3.14—Foam application
- 3.15—Construction hazards

Chapter 4—Shotcrete dome, p. 334.3R-9

- 4.1—General
- 4.2—Reinforcement material and size
- 4.3—Clear spacing between bars
- 4.4—Splices

ACI Committee Reports, Guides, Standard Practices, and Commentaries are intended for guidance in planning, designing, executing, and inspecting construction. This document is intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. The American Concrete Institute disclaims any and all responsibility for the stated principles. The Institute shall not be liable for any loss or damage arising therefrom.

Reference to this document shall not be made in contract documents. If items found in this document are desired by the Architect/Engineer to be a part of the contract documents, they shall be restated in mandatory language for incorporation by the Architect/Engineer.

ACI 334.3R-05 became effective September 16, 2005.
Copyright © 2005, American Concrete Institute.

All rights reserved including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by electronic or mechanical device, printed, written, or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permission in writing is obtained from the copyright proprietors.

- 4.5—Cover
- 4.6—Preliminary reinforcement mat (premat)
- 4.7—Shell reinforcement
- 4.8—Preconstruction shotcrete tests
- 4.9—Shotcrete compression tests
- 4.10—Proportions and materials
- 4.11—Field practice
- 4.12—Nozzle operator qualifications
- 4.13—Shotcrete operation
- 4.14—Discharge time
- 4.15—Joints
- 4.16—Multi-pass technique
- 4.17—Curing
- 4.18—Shotcrete placement tolerance
- 4.19—Shotcrete damage
- 4.20—Completion

Chapter 5—References, p. 334.3R-13

- 5.1—Referenced standards and reports
- 5.2—Cited references

CHAPTER 1—GENERAL

1.1—Introduction (Fig. 1.1)

For centuries, arched and dome-shaped structures have efficiently enclosed large clear-span volumes. The strength of compound-curved surfaces allowed early builders to construct self-supporting thin-shell buildings from a variety of materials. Due to the tremendous amount of time and effort needed to create the desired shapes, construction of these thin-shelled structures sometimes spanned several decades.

Knowledge of the design and construction of thin-shell concrete structures has greatly increased over the past 100 years, both from research and practical experience. In the past 40 to 50 years, the use of inflated forms has allowed shells to be constructed more economically (South 1990). This new type of construction process presents new challenges and concerns. Safety measures and construction tolerances are addressed in this report for many types of systems using inflatable forms.

1.2—Scope (Fig. 1.2)

This report contains the lessons learned in the construction of thin-shell concrete dome structures using inflated forms. As this method of construction continues to gain popularity, additional research is needed to increase understanding of the behavior of this type of shell so that inflated-form structures continue to meet adequate levels of safety and serviceability. Included are construction procedures, tolerances, and design checks to ensure that the finished structure meets adequate safety and serviceability levels. This document focuses primarily on inflated form thin shells using polyurethane foam as part of the construction process. Many structures are built using fabric forms where the concrete is applied directly to the form either from the outside or the inside. These general guidelines apply to all methods.

1.3—History (Fig. 1.3)

Since the early 1940s, several methods of construction using inflatable forms have been used. These methods include



Fig. 1.1—Faith Chapel Christian Center, Birmingham, Ala.: 280 ft (85.35 m) diameter and 72 ft (22 m) tall that includes a 3200-seat sanctuary, classrooms, and an administration building.



Fig. 1.2—Price City Works Complex, Price, Utah. Four domes: 130 x 43 ft (40 x 13.1 m) fire station; 130 x 43 ft (40 x 13.1 m) storage facility; 130 x 43 ft (40 x 13.1 m) maintenance shop; and 90 x 40 ft (27 x 12.2 m) office and administration building.



Fig. 1.3—U.S. Borax and Chemical Co., Boron, Calif.: two 20,000 ton (18,000 tonne) borax storage domes, 150 x 79 ft (45.7 x 24.1 m).

shotcrete applied to the form exterior, and foam and shotcrete applied to the form interior.

In 1942, Wallace Neff received a patent on a system where the form was inflated to the shape of the structure, and then the reinforcing bar and shotcrete were placed on the exterior of the form (Neff 1942). Dante Bini later developed and received a patent on a system where the reinforcement and concrete were placed on the exterior of the form before it was inflated. It was then raised by air pressure to form the dome (Fig. 1.4) (Bini 1986).

In 1972, Lloyd Turner received a patent on a process in which the inflated form was sprayed with foam on the inside to a desired thickness creating a self-supporting foam dome