

**Specification for Carbon and Glass
Fiber-Reinforced Polymer (FRP)
Materials Made by Wet Layup for
External Strengthening of Concrete
and Masonry Structures**

An ACI Standard

Reported by ACI Committee 440



First Printing
May 2014

American Concrete Institute®
Advancing concrete knowledge

Specification for Carbon and Glass Fiber-Reinforced Polymer (FRP) Materials Made by Wet Layup for External Strengthening of Concrete and Masonry Structures

Copyright by the American Concrete Institute, Farmington Hills, MI. All rights reserved. This material may not be reproduced or copied, in whole or part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. In spite of these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI via the errata website at www.concrete.org/committees/errata.asp. Proper use of this document includes periodically checking for errata for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided “as is” without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations with regard to health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

Participation by governmental representatives in the work of the American Concrete Institute and in the development of Institute standards does not constitute governmental endorsement of ACI or the standards that it develops.

Order information: ACI documents are available in print, by download, on CD-ROM, through electronic subscription, or reprint and may be obtained by contacting ACI.

Most ACI standards and committee reports are gathered together in the annually revised ACI Manual of Concrete Practice (MCP).

American Concrete Institute
38800 Country Club Drive
Farmington Hills, MI 48331
U.S.A.
Phone: 248-848-3700
Fax: 248-848-3701

www.concrete.org

ISBN: 978-0-87031-892-4

Specification for Carbon and Glass Fiber-Reinforced Polymer (FRP) Materials Made by Wet Layup for External Strengthening of Concrete and Masonry Structures

An ACI Standard

Reported by ACI Committee 440

Carol K. Shield*, Chair

William J. Gold*, Secretary

Tarek Alkhrdaji
Charles E. Bakis*
Lawrence C. Bank
Abdeldjelil Belarbi
Brahim Benmokrane
Luke A. Bisby
Gregg J. Blaszak*
Hakim Bouadi
Timothy E. Bradberry
Gordon L. Brown Jr.
Vicki L. Brown
John P. Busel
Raafat El-Hacha
Garth J. Fallis
Amir Z. Fam
Nabil F. Grace
Mark F. Green
Zareh B. Gregorian
Doug D. Gremel
Shawn P. Gross

H. R. Trey Hamilton III
Issam E. Harik
Kent A. Harries
Mark P. Henderson
Bohdan N. Horeczko
Michael W. Lee
Maria E. Lopez de Murphy
Ibrahim M. Mahfouz
Amir Mirmiran
John J. Myers
Antonio Nanni*
Ayman M. Okeil
Carlos E. Ospina
Renato Parretti
Max L. Porter
Andrea Prota
Hayder A. Rasheed
Sami H. Rizkalla
Rajan Sen
Rudolf Seracino

Pedro F. Silva
Khaled A. Soudki
Samuel A. Steere III
Jay Thomas
Houssam A. Toutanji
J. Gustavo Tumialan
Milan Vatovec
David White
Sarah E. Witt†

Consulting members
P. N. Balaguru
Craig A. Ballinger
Harald G. F. Budelmann
C. J. Burgoyne
Elliot P. Douglas
Rami M. Elhassan
David M. Gale
Russell Gentry
Arie Gerritse

Srinivasa L. Iyer
Koichi Kishitani
Howard S. Kliger
Kyuichi Maruyama
Antoine E. Naaman
Hajime Okamura
Mark A. Postma
Ferdinand S. Rostasy
Surendra P. Shah
Mohsen Shahawy
Yasuhisa Sonobe
Minoru Sugita
Luc R. Taerwe
Ralejs Tepfers
Taketo Uomoto
Paul Zia

*Contributing authors.
†Task Group Chair.

This material specification covers the requirements for carbon and glass fiber-reinforced polymer (FRP) systems made by the wet layup process. These systems are externally bonded to concrete or masonry structures and intended for the structural strengthening of them.

Keywords: carbon fiber; fiber-reinforced polymer (FRP); glass fiber; masonry; wet layup.

CONTENTS

1—SCOPE, p. 2

2—DEFINITIONS, p. 2

3—REFERENCED STANDARDS, p. 2

4—CLASSIFICATION, p. 2

ACI 440.8M was adopted November 29, 2013 and published May 2014.

Copyright © 2014, American Concrete Institute.

All rights reserved including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by electronic or mechanical device, printed, written, or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permission in writing is obtained from the copyright proprietors.

5—MATERIALS AND MANUFACTURE, p. 3**6—PHYSICAL PROPERTIES, p. 3****7—MECHANICAL PROPERTIES, p. 3****8—DURABILITY PROPERTIES, p. 3****9—SAMPLING, FREQUENCY, AND NUMBER OF SPECIMENS, p. 3****10—PRODUCT DATA SHEETS, p. 4****1—SCOPE**

1.1 This specification describes permitted constituent materials, minimum performance requirements of those constituent materials, and minimum performance requirements for carbon fiber-reinforced polymer (CFRP) and glass fiber-reinforced polymer (GFRP) laminae made from those constituent materials using the wet layup process.

1.2 This specification only covers the fabric reinforcement and saturating resin that comprise the FRP system. Primers and putty fillers are excluded.

1.3 This specification applies to FRP laminae consisting of one ply of continuous, unidirectional fiber reinforcement and saturating resin fabricated using the wet layup process. Laminae with fibers in more than one direction that are intended to provide strength in more than one direction are excluded.

1.4 Precured FRP systems are not covered by this specification.

1.5 Hybrid FRP systems consisting of more than one type of fiber are excluded.

1.6 Only FRP laminae with epoxy resins are covered by this specification.

1.7 Values in this specification are stated in SI units. A companion specification in in.-lb units is available.

2—DEFINITIONS

2.1 The following definitions govern in this specification. For definitions not given below, refer to “ACI Concrete Terminology,” www.concrete.org/Tools/ConcreteTerminology.aspx. For definitions used in but not specific to this specification, refer to ASTM C904.

fabric reinforcement—reinforcing fibers in fabric form.

fiber-reinforced polymer lamina—a single layer of composite material made by combining fabric reinforcement and saturating resin matrix.

fiber-reinforced polymer system—the product fabricated using the wet layup method with the FRP system manufacturer’s fiber reinforcement and saturating resin per the FRP system manufacturer’s instructions.

mean property—a property value provided by the manufacturer no greater than the mean of results obtained by a specified test method for at least the specified number of specimens. *Discussion*—This value is applicable to FRP chord tensile stiffness, resin properties, and for calculating retention values for durability.

ply—a single layer of fiber reinforcement.

roving—a parallel bundle of continuous yarns, tows, or fibers with little or no twist.

tow—an untwisted bundle of continuous filaments.

ultimate property—a property value provided by the manufacturer no greater than the mean minus three standard deviations of results obtained by a specified test method for at least the specified number of specimens. *Discussion*—This definition is applicable to maximum tensile force.

wet layup—a manufacturing process where dry fabric fiber reinforcement is impregnated on-site with a saturating resin matrix and then cured in-place.

3—REFERENCED STANDARDS**3.1 ASTM International**

C581-03(2008)—Standard Practice for Determining Chemical Resistance of Thermosetting Resins Used in Glass-Fiber-Reinforced Structures Intended for Liquid Service

C904-01(2012)—Standard Terminology Relating to Chemical-Resistant Nonmetallic Materials

D638-10—Standard Test Method for Tensile Properties of Plastics

D790-10—Standard Test Methods for Flexural Properties of Unreinforced and Reinforced Plastics and Electrical Insulating Materials

D1141-98(2013)—Standard Practice for the Preparation of Substitute Ocean Water

D2247-11—Standard Practice for Testing Water Resistance of Coatings in 100% Relative Humidity

D3045-92(2010)—Standard Practice for Heat Aging of Plastics Without Load

D3776/D3776M-09a(2013)—Standard Test Methods for Mass Per Unit Area (Weight) of Fabric

D7565/D7565M-10—Standard Test Method for Determining Tensile Properties of Fiber Reinforced Polymer Matrix Composites Used for Strengthening of Civil Structures

E1640-13—Standard Test Method for Assignment of the Glass Transition Temperature by Dynamic Mechanical Analysis

G153-13—Standard Practice for Operating Enclosed Carbon Arc Light Apparatus for Exposure of Nonmetallic Materials.

3.2 International Code Council—Evaluation Service (ICC-ES)

AC125—Acceptance Criteria for Concrete and Reinforced and Unreinforced Masonry Strengthening Using Externally Bonded Fiber-Reinforced Polymer (FRP) Composite Systems

4—CLASSIFICATION

4.1 Fiber-reinforced polymer systems shall be classified according to their fiber reinforcement composition with the first letter of the acronym designating fiber type as follows:

- a) CFRP—Carbon fiber-reinforced polymer systems;
- b) GFRP—Glass fiber-reinforced polymer systems