

**ACI 522.1M-13**

(metric)

# **Specification for Pervious Concrete Pavement**

An ACI Standard

Reported by ACI Committee 522



**American Concrete Institute®**



**American Concrete Institute®**  
*Advancing concrete knowledge*

First Printing  
October 2013

## **Specification for Pervious Concrete Pavement**

Copyright by the American Concrete Institute, Farmington Hills, MI. All rights reserved. This material may not be reproduced or copied, in whole or part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. In spite of these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI via the errata website at [www.concrete.org/committees/errata.asp](http://www.concrete.org/committees/errata.asp). Proper use of this document includes periodically checking for errata for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided “as is” without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations with regard to health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

Participation by governmental representatives in the work of the American Concrete Institute and in the development of Institute standards does not constitute governmental endorsement of ACI or the standards that it develops.

Order information: ACI documents are available in print, by download, on CD-ROM, through electronic subscription, or reprint and may be obtained by contacting ACI.

Most ACI standards and committee reports are gathered together in the annually revised ACI Manual of Concrete Practice (MCP).

**American Concrete Institute**  
**38800 Country Club Drive**  
**Farmington Hills, MI 48331**  
**U.S.A.**  
**Phone: 248-848-3700**  
**Fax: 248-848-3701**

**[www.concrete.org](http://www.concrete.org)**

ISBN-13: 978-0-87031-848-1

The official version of this standard is the English language version using inch-pound units published by the American Concrete Institute.

# Specification for Pervious Concrete Pavement

An ACI Standard

Reported by ACI Committee 522

Matthew A. Offenberg, Chair  
Charles A. Weiss Jr., Vice Chair

Narayanan Neithalath, Secretary

William L. Arent  
Bob J. Banka  
William D. Brant  
Heather J. Brown  
Javier Castro  
Manoj Chopra  
John F. Cook  
Michael S. Davy  
Norbert J. Delatte  
Aly Ibrahim Eldarwish  
Scott J. Erickson  
Dale Fisher

Walter H. Flood IV  
Bruce A. Glaspey  
Liv Haselbach  
Omer Heracklis  
Daniel J. Huffman  
John T. Kevern  
Frank Lennox  
Milan R. Lipensky  
John R. Love III  
Darmawan Ludirdja  
Allyn C. Luke  
Brian G. Lutey

Kamyar C. Mahboub  
Andrew E. Marks  
Luis A. Mata  
Oon-Soo Ooi  
Joseph E. Rottman  
Thomas L. Rozsits  
George W. Seegebrecht  
David M. Suchorski  
Diep T. Tu  
Christopher R. Tull  
Robert Louis Varner  
Don J. Wade

W. Jason Weiss  
Kevin D. Wolf  
Peter T. Yen

*Consulting members*  
Bruce K. Ferguson  
N. Mike Jackson  
Scott M. Palotta  
Stephen F. Rohrbach  
Andy K. Youngs

*This Specification covers materials, preparation, forming, placing, finishing, jointing, curing, and quality control of pervious concrete pavement. Provisions governing testing, evaluation, and acceptance of pervious concrete pavement are included.*

*This Reference Specification can be made applicable by citing it in the Project Specifications. The Architect/Engineer can supplement this reference specification, as needed, by specifying individual project requirements.*

**Keywords:** construction; curing; inspection; jointing; parking lots; testing.

## CONTENTS

(nonmandatory portion follows)

### PART 1—GENERAL, p. 2

- 1.1—Scope, p. 2
- 1.2—Definitions, p. 2
- 1.3—Referenced standards, p. 2
- 1.4—Submittals, p. 3
- 1.5—Quality control, p. 3

### PART 2—PRODUCTS, p. 4

- 2.1—Subbase, p. 4
- 2.2—Pervious concrete, p. 4
- 2.3—Isolation joint material, p. 4
- 2.4—Forms, p. 4
- 2.5—Polyethylene curing sheet, p. 4

### PART 3—EXECUTION, p. 4

- 3.1—Subgrade preparation, p. 4
- 3.2—Subbase, p. 5

- 3.3—Setting formwork, p. 5
- 3.4—Batching, mixing, and delivery, p. 5
- 3.5—Placing and finishing fixed-form pavement, p. 5
- 3.6—Placing and finishing slipform pavement, p. 5
- 3.7—Final surface texture, p. 5
- 3.8—Edging, p. 5
- 3.9—Tolerances, p. 5
- 3.10—Curing, p. 5
- 3.11—Cold-weather construction, p. 5
- 3.12—Jointing, p. 5
- 3.13—Opening to traffic, p. 6

### NOTES TO SPECIFIER, p. 6

General Notes, p. 6

### FOREWORD TO CHECKLISTS, p. 6

### MANDATORY REQUIREMENTS CHECKLIST, p. 7

### SUBMITTALS CHECKLIST, p. 7

(mandatory portion follows)

ACI 522.1M-13 supersedes ACI 522.1-08, became effective May 22, 2013, and was published October 2013.

Copyright © 2013, American Concrete Institute.

All rights reserved including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by electronic or mechanical device, printed, written, or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permission in writing is obtained from the copyright proprietors.

## PART 1—GENERAL

### 1.1—Scope

**1.1.1** This Specification provides requirements for the construction of pervious concrete pavement.

**1.1.2** If the requirements of this Specification conflict with the Contract Documents, the Contract Documents shall govern.

**1.1.3** Values in this Specification are stated in SI units. A companion Specification in inch-pound units is also available.

**1.1.4** Plus (+) tolerance increases the amount or dimension to which it applies, or raises a deviation from level. Minus (–) tolerance decreases the amount or dimension to which it applies, or lowers a deviation from level. Where only one signed tolerance is specified (+ or –), there is no specified tolerance in the opposing direction.

### 1.2—Definitions

**acceptable** or **accepted**—determined to be satisfactory by architect/engineer.

**acceptance**—acknowledgment by Architect/Engineer that submittal or completed Work is acceptable.

**Architect/Engineer**—the architect, engineer, architectural firm, or engineering firm developing contract documents or administering the work under contract documents, or both.

**Contract Documents**—a set of documents supplied by owner to bidders during bidding phase of a construction project. These documents include general requirements, contract forms, contract conditions, specifications, drawings, and addenda.

**Contractor**—the person, firm, or entity under contract for construction of the Work.

**construction joint**—the surface where two successive placements of concrete meet, across which it may be desirable to achieve bond.

**contraction joint**—formed, sawed, or tooled groove in a concrete structure to create a weakened plane to regulate the location of cracking.

**design void content**—the percentage of voids of a unit volume of pervious concrete based on the theoretical mixture proportions and design density and where the unit volume includes the volume of the solids and the voids.

**early-entry dry-cut saw**—a tool designed to produce joints in concrete commencing 1 to 4 hours after finishing.

**hardened density**—the dry density of pervious concrete as determined by Paragraphs 8.3 and 9.3 of ASTM C140-12.

**hydration-stabilizing admixtures**—set-retarding admixtures, conforming to ASTM C494/C494M Type B or D, that can predictably reduce the hydration rate of cement for applications requiring the management of time of setting of returned concrete, reducing the hydration rate of cement fines in water from concrete production, or for applications requiring extended delivery time of ready mixed concrete.

**isolation joint**—a normally vertical interface allowing relative movement without transferring sufficient tension,

compression, or traction forces to negatively affect the performance of a pavement structure.

**Owner**—the corporation, association, partnership, individual, public body, or authority for whom the Work is constructed.

**panel**—a concrete element that is relatively thin with respect to other dimensions and is bordered by joints or edges.

**permitted**—accepted by or acceptable to Architect/Engineer, usually pertaining to a request by Contractor, or when specified in Contract Documents.

**pervious pavement**—a pavement comprising material with sufficient continuous voids to allow water to pass from the surface to the underlying layers.

**Project Drawings**—graphic presentation of project requirements.

**Project Specification**—written document that details requirements for the Work in accordance with service parameters and other specific criteria.

**referenced standards**—standardized mandatory-language documents of a technical society, organization, or association, including codes of local or state authorities, which are incorporated by reference in Contract Documents.

**subbase**—the layer in a pavement system between the subgrade and the base course, or between the subgrade and a pervious concrete pavement.

**submittal**—document or material provided to Architect/Engineer for review and acceptance.

**Work**—the entire construction or separately identifiable parts thereof required to be furnished under Contract Documents.

### 1.3—Referenced standards

**1.3.1** Standards of ACI and ASTM cited in this Specification are listed by name and designation, including year.

#### 1.3.1.1 *American Concrete Institute*

306.1-90—Standard Specification for Cold Weather Concreting

#### 1.3.1.2 *ASTM International*

C42/C42M-13—Standard Test Method for Obtaining and Testing Drilled Cores and Sawed Beams of Concrete

C94/C94M-13—Standard Specification for Ready Mixed Concrete

C140-12—Standard Test Methods for Sampling and Testing Concrete Masonry Units and Related Units

C150/C150M-12—Standard Specification for Portland Cement

C171-07—Standard Specification for Sheet Materials for Curing Concrete

C172/C172M-10—Standard Practice for Sampling Freshly Mixed Concrete

C174/C174M-12—Standard Test Method for Measuring Thickness of Concrete Elements Using Drilled Concrete Cores

C260/C260M-10—Standard Specification for Air-Entraining Admixtures for Concrete

C494/494M-12—Standard Specification for Chemical Admixtures for Concrete