

An ACI Technical Publication

SYMPOSIUM VOLUME



Recent Developments in High Strain Rate
Mechanics and Impact Behavior of Concrete

SP-347

Editors:
Eric Jacques and Mi G. Chorzepa



American Concrete Institute
Always advancing

Recent Developments in High Strain Rate Mechanics and Impact Behavior of Concrete

Sponsored by
ACI 370 Committee

ACI Virtual Concrete Convention
March 28-April 1, 2021

Editors:
Eric Jacques and
Mi G. Chorzepa



American Concrete Institute
Always advancing

SP-347

First printing, March 2021

Discussion is welcomed for all materials published in this issue and will appear ten months from this journal's date if the discussion is received within four months of the paper's print publication. Discussion of material received after specified dates will be considered individually for publication or private response. ACI Standards published in ACI Journals for public comment have discussion due dates printed with the Standard.

The Institute is not responsible for the statements or opinions expressed in its publications. Institute publications are not able to, nor intended to, supplant individual training, responsibility, or judgment of the user, or the supplier, of the information presented.

The papers in this volume have been reviewed under Institute publication procedures by individuals expert in the subject areas of the papers.

Copyright © 2021
AMERICAN CONCRETE INSTITUTE
38800 Country Club Dr.
Farmington Hills, Michigan 48331

All rights reserved, including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by any electronic or mechanical device, printed or written or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permission in writing is obtained from the copyright proprietors.

Printed in the United States of America

Editorial production: Gail L. Tatum

ISBN-13: 978-1-64195-134-0

PREFACE

Recent Developments in High Strain Rate Mechanics and Impact Behavior of Concrete

This Symposium Volume reports on the latest developments in the field of high strain rate mechanics and behavior of concrete subject to impact loads. This effort supports the mission of ACI Committee 370 “Blast and Impact Load Effects” to develop and disseminate information on the design of concrete structures subjected to impact, as well as blast and other short-duration dynamic loads. Concrete structures can potentially be exposed to accidental and malicious impact loads during their lifetimes, including those caused by ballistic projectiles, vehicular collision, impact of debris set in motion after an explosion, falling objects during construction and floating objects during tsunamis and storm surges. Assessing the performance of concrete structures to implement cost-effective and structurally-efficient protective measures against these extreme impacting loads necessitates a fundamental understanding of the high strain rate behavior of the constituent materials and of the characteristics of the local response modes activated during the event.

This volume presents fourteen papers which provide the reader with deep insight into the state-of-the-art experimental research and cutting-edge computational approaches for concrete materials and structures subject to impact loading. Invited contributions were received from international experts from Australia, Canada, China, Czech Republic, Germany, South Korea, Switzerland, and the United States. The technical papers cover a range of cementitious materials, including high strength and ultra-high strength materials, reactive powder concrete, fiber-reinforced concrete, and externally bonded cementitious layers and other coatings. The papers were to be presented during two technical sessions scheduled for the ACI Spring 2020 Convention in Rosemont, Illinois, but the worldwide COVID-19 pandemic disrupted those plans.

The editors thank the authors for their outstanding efforts to showcase their most current research work with the concrete community, and for their assistance, cooperation, and valuable contributions throughout the entire publication process. The editors also thank the members of ACI Committee 370, the reviewers, and the ACI staff for their generous support and encouragement throughout the preparation of this volume.

TABLE OF CONTENTS

SP-347-1:

On the Rate Sensitive Fracture Behavior of Strain-Hardening Cement-Based Composites (SHCC) Depending on Fiber Type and Matrix Composition..... 1-20
Authors: Iurie Curosu, Viktor Mechtcherine, Daniele Forni, Simone Hempel and Ezio Cadoni

SP-347-2:

High Strain Rate Properties of CFRP Sheets Surface Bonded to Concrete21-38
Authors: Jonathan Harman, Emmanuella O. Atunbi, and Alan Lloyd

SP-347-3:

Using Steel Fibres to Increase the Projectile Impact Resistance of Cementitious Composites.....39-58
Authors: Radoslav Sovják, Sebastjan Kravanja, and Jan Zatloukal

SP-347-4:

Predicting the Response of Concrete Barriers to Rigid Projectile Impacts Using AEM.....59-84
Authors: Tarek Kewaisy, Ayman Elfouly, and Ahmed Khalil

SP-347-5:

Cracked Continuum Modeling of Reinforced Concrete Elements under Impact..... 85-105
Authors: Serhan Guner, Trevor D. Hrynyk, and Andac Lulec

SP-347-6:

Distinguished Impact Response of Hollow Reinforced Concrete Beams under Impact Loading.....106-126
Authors: Thong M. Pham, Tin V. Do, and Hong Hao

SP-347-7:

Damage Accumulation Comparison of Fiber-Reinforced Concrete Using Repeated Drop Impact Testing.....127-137
Authors: Andrew D. Sorensen, Robert J. Thomas, Ryan Langford, and Abdullah Al-Sarfin

SP-347-8:

Response of Reinforced Concrete Columns against Hypervelocity Impacts by EFPs..... 138-154
Authors: Alex Remennikov and Edward Chern Jinn Gan

SP-347-9:

Impact Response of SC Panels under Local Punching Failure: Experiments and FE Analyses..... 155-175
Authors: Quanquan Guo, Chengwei Guo, Xuqiang Dou, and Chuanchuan Hou

SP-347-10:

Structural Behavior of TL-4 Recycled Tire Chip and Fiber Reinforced Concrete Single Slope Barriers 176-190
Authors: Grace Darling, Stephan A. Durham, and Mi G. Chorzepa

SP-347-11:

Impact Performance of Recycled Rubber Tire Chip and Fiber-Reinforced
Cementitious Composites191-214
Authors: Victor Lopez, Mi G. Chorzepa, and Stephan A. Durham

SP-347-12:

Impact Resistance and Strength of SCC Containing Crumb and Powder Rubbers215-229
Author: Assem A. A. Hassan

SP-347-13:

Assessment of Material Flow during Projectile Penetration of Concrete Targets230-248
Authors: Girum Urgessa and Robert Sobeski

SP-347-14:

Hard and Soft Projectile Impact Simulation of Prestressed Concrete Panels.....249-260
Authors: Seong Ryong Ahn and Thomas H.-K. Kang

On the Rate Sensitive Fracture Behavior of Strain-Hardening Cement-Based Composites (SHCC) Depending on Fiber Type and Matrix Composition

Iurie Curosu, Viktor Mechtcherine, Daniele Forni, Simone Hempel and Ezio Cadoni

Synopsis: Strain-hardening cement-based composites (SHCC) represent a special type of fiber reinforced concretes, whose post-elastic tensile behavior is characterized by the formation of multiple, fine cracks under increasing loading up to failure localization. The high inelastic deformability in the strain-hardening phase together with the high damage tolerance and energy dissipation capacity make SHCC promising for applications involving dynamic loading scenarios, such as earthquake, impact or blast.

However, the main constitutive phases of SHCC, i.e. matrix, fibers and interphase between them, are highly rate sensitive. Depending on the SHCC composition, the increase in loading rates can negatively alter the balanced micromechanical interactions, leading to a pronounced reduction in strain capacity. Thus, there is need for a detailed investigation of the strain rate sensitivity of SHCC at different levels of observation for enabling a targeted material design with respect to high loading rates.

The crack opening behavior is an essential material parameter for SHCC, since it defines to a large extent the tensile properties of the composite. In the paper at hand, the rate effects on the crack opening and fracture behavior of SHCC are analyzed based on quasi-static and impact tensile tests on notched specimens made of three different types of SHCC. Two SHCC consisted of a normal-strength cementitious matrix and were reinforced with polyvinyl-alcohol (PVA) and ultra-high molecular weight polyethylene (UHMWPE) fibers, respectively. The third type consisted of a high-strength cementitious matrix and UHMWPE fibers. The dynamic tests were performed in a split Hopkinson tension bar and enabled an accurate description of the crack opening behavior in terms of force-displacement relationships at displacement rates of up to 6 m/s (19.7 ft/s).

Keywords: SHCC, fiber reinforcement, strain-hardening, PVA, UHMWPE, impact, split Hopkinson tension bar, fracture energy

Iurie Curosu is a Postdoctoral Researcher at the Institute of Construction Materials, Faculty of Civil Engineering at the Technische Universität Dresden, Germany. His research activity is closely related to the multidisciplinary Research Training Group GRK 2250 “Mineral-bonded composites for enhanced structural impact safety”. His research interests encompass high-performance fiber reinforced cementitious composites, such as Strain-Hardening Cement-Based Composites (SHCC) and Textile Reinforced Concrete (TRC). In the context of severe dynamic loading scenarios and structural strengthening with thin, impact resistant overlays, he works on material analysis and design by means of multi-scale, experimental and numerical methods.

Viktor Mechtcherine is Professor and Director of the Institute of Construction Materials, Faculty of Civil Engineering at the Technische Universität Dresden, Germany, since 2006. He is coordinator of the Research Training Group GRK 2250 “Mineral-bonded composites for an enhanced structural impact safety” sponsored by the German Research Foundation (DFG). Furthermore, he is RILEM Fellow, member of Science Academy of Saxony and Russian Academy of Engineering, chair of RILEM TC 260-RSC ‘Recommendation for Use of Superabsorbent Polymers in Concrete Construction’, and member of Editorial Boards of the Journals ‘Cement and Concrete Composites’ and ‘Materials and Structures’.

Daniele Forni is a Researcher and Lecturer at the University of Applied Sciences of Southern Switzerland (Lugano). He received his MSc in Civil Engineering and PhD in Structural Engineering from Politecnico di Torino. His teaching covers the fundamentals of structural mechanics (statics, theory of structures, masonry). His research interests include dynamic behavior of materials and structures.

Simone Hempel is a Senior Researcher at the Institute of Construction Materials at the TU Dresden, Germany. Her research focus lies on analytical investigations of the microstructure, composition and morphology of construction materials, such as concrete and cementitious composites.

Ezio Cadoni is Professor at the University of Applied Sciences of Southern Switzerland (Lugano). He received his MSc in Civil Engineering from the University of Cagliari and PhD in Structural Engineering from Politecnico di Torino. He founded the DynaMat Laboratory. He is Deputy-Chair of RILEM IEC Committee and Past President of DYMAT association. His teaching covers the fundamentals of structural mechanics (statics, theory of structures, masonry, and mechanics of materials). His research interests include dynamic behavior of materials and structures, impact.

INTRODUCTION

SHCC consist of fine-grained cementitious matrices and short, high-performance polymer fibers in volume fractions of up to 2% [1]. The micromechanics-based material design aims a balance between the cracking behavior of the cementitious matrix and crack bridging behavior of the fibers, in this way ensuring a pronounced tensile ductility through the successive formation of fine, densely spaced cracks under increasing tensile loading. The remarkably high strain capacity of SHCC in combination with their favorable fresh-state properties allows their efficient application not just as main material in structural elements but also as thin strengthening layers on existing structures [2-6], including those prone to severe dynamic actions [7-9].

However, under increasing loading rates, the disproportionate changes of the components’ properties alter the micromechanical balance as achieved for the case of quasi-static loading [10]. This might yield negative effects on the composite tensile behavior [11-14]. For the formulation of reliable material design concepts with respect to increased loading rates, the rate effects at the level of constituents, of the collective crack bridging and of the resulting composite behavior must be investigated and quantified.

Several studies were reported on the effect of increasing loading rates on the tensile behavior of SHCC, most of them being conducted in the range of low and moderate loading rates [9,11,13]. With regard to impact tensile loading, few reports were published [12,15,16], among which only Curosu et al. [16] and Heravi et al. [17] offered a detailed quantitative characterization of the impact tensile behavior of various SHCC in form stress-strain curves.

The crack opening behavior and fracture energy of notched SHCC specimens were only investigated in [12,15] in Hopkinson bar spall experiments. Using the evaluation methodology proposed by Schuler et al. [18], the specific fracture energy was derived from the impulse transfer between the separated fragments of notched specimens. These investigations provided valuable insights into the effects of high loading rates on the tensile behavior of SHCC