

ACI Conventions

ACI conventions provide a forum for networking, learning the latest in concrete technology and practices, renewing old friendships, and making new ones. At each of ACI's two annual conventions, technical and educational committees meet to develop the standards, reports, and other documents necessary to keep abreast of the ever-changing world of concrete technology.

With over 1,300 delegates attending each convention, there is ample opportunity to meet and talk individually with some of the most prominent persons in the field of concrete technology. For more information about ACI conventions, visit www.aciconvention.org.

ACI
WEB SESSIONS



American Concrete Institute®
Advancing concrete knowledge

Emerging Technologies

ACI Fall 2012 Convention
October 21 – 24, Toronto, ON

ACI
WEB SESSIONS

Concrete Pavements Containing PLC & SCM – A Review after 3 & 4 years

by

Ashlee Hossack, Ph.D. Candidate, University of Brunswick, Fredericton, NB, Canada

ACI
WEB SESSIONS

Concrete Pavements Containing PLC & SCM – A Review after 3 & 4 years

Michael Thomas, Ashlee Hossack, Kevin Cail, Anik Delagrave, Laurent Barcelo, Bruce Blair, Ken Kazanis




Concrete Pavements Containing PLC & SCM – A Review after 3 & 4 years

- In 2008 CSA allowed the replacement of up to 15% Portland cement with limestone
- Replacement of Portland cement with interground limestone can reduce CO₂ by 10%
- Extensive laboratory research has been conducted; this project demonstrates the field performance of concretes with varying limestone and SCM replacement levels

8


Pavements

PLC-SCM pours using 3 different Lafarge cements from plants across Canada

- Bath, Ontario
 - Pavement placed in Gatineau, Quebec
 - October 2008
- Exshaw, Alberta
 - September 2009
- Brookfield, Nova Scotia
 - October 2009

9

Pavement Locations



10

Limestone and SCM Replacement



Brookfield Cement Plant, NS

11

Limestone and SCM Replacement

Brookfield, NS


	Clinker Content (%)					
	Gypsum (%)	Limestone (%)	Slag (%)	0 Fly ash	15% FA	20% FA
PC	5	4	0	91	76	71
PC-slag	5	0	15	80	65	60
PLC-slag	5	12	15	68	53	48

- Slag was interground
 - Fly ash added at plant (0%, 15%, 20%)
- W/CM from 0.42-0.44
- Slump: 60-80mm (2 ¼ - 3 ¼ in.)
- Air: 5.8-6.6%

Field samples with PC-slag and PLC-slag only, lab samples with all 3 cements

12

Limestone and SCM Replacement



13

Limestone and SCM Replacement



Gatineau Ready-mix Plant, QC

14


Limestone and SCM Replacement

Gatineau, QC

	Clinker Content (%)				
	Limestone (%)	0	25	40	50
GU	3.5%	92	69	55	46
GUL	12%	84	63	50	42

- SCM blend of 2/3 slag + 1/3 fly ash
- W/CM from 0.44-0.45
- Slump: 75-100mm (3-4 in.)
- Air: 6.0-6.8%

15












Limestone and SCM Replacement







Exshaw, AB

	Limestone (%)	Clinker Content (%)			
		Fly ash Content (%)			
		0	15	25	30
PC	4	91	76	66	61
PLC	12	83	68	58	53

- Fly ash added at plant
- W/CM = 0.37-0.42







Conclusions of Study

- The addition of SCMs had a significant impact on the performance of PC and PLC concretes
- PC and PLC blend concretes displayed very similar performance in all cases
 - Compressive strength within 10MPa for companion mixes
 - All SCM blend concrete had very low chloride permeability regardless of limestone content
- The PLC with up to 12% interground limestone achieved equal performance to PC
- The limestone content did not alter the effect that SCMs had on concrete performance

34