

Product Showcase

Cleaning Equipment & Tools

Steam Jenny Electric-Powered, Direct-Driven Pressure Washers

Steam Jenny's line of electric-powered, direct-driven pressure washers can be operated in enclosed areas where gas-powered machines cannot be used. The pressure washers are powered by Marathon or Baldor electric motors, depending on the model, and range from 1.5 to 10 hp. They are available with either single-phase ground-fault circuit interrupter (GFCI) or three-phase power requirements. Pressure ratings for the units range between 1000 and 4000 psi (6.9 and 27.6 MPa), and flow rates vary between 1.5 and 4.8 gpm (5.7 and 18.2 L/min). An optional feature allows customers to choose pressure and flow ratings. Standard features include a seven-gauge steel chassis, heavy-duty unloader valve, safety relief valve, thermal relief valve, and high-capacity inlet in-line water strainer. The pressure washers also come with an insulated trigger gun, a 50 ft (15.2 m) hose with quick coupling, and a series of 0- to 40-degree-angle color-coded nozzles. Options include a rotary (turbo) nozzle, rotary brush, dual lance with variable pressure, low-water cutoff, pulse-dampening accumulator, and chemical injection kits.

—Steam Jenny, www.steamjenny.com



Sure Klean ReVeal

Sure Klean® ReVeal from PROSOCO safely and effectively cleans masonry, stone, and a variety of other architectural substrates. It is formulated to clean atmospheric and carbon staining from most kinds of masonry and stone, including architectural concrete and concrete block. It can also remove soiling and hard-to-remove deposits from window glass, and it is safe for use around most architectural metals, virtually eliminating the need to specially protect and cover many nonmasonry substrates and materials during the cleaning process. Safer and less corrosive than conventional restoration cleaners based on hydrofluoric acid or ammonium bifluoride, ReVeal comes in liquid form rather than as a gel, facilitating a shorter dwell time that allows users to finish jobs faster. ReVeal is available in 1 and 5 gal. (3.8 and 18.9 L) pails and 55 gal. (208 L) drums.

—PROSOCO, www.prosoco.com



Ion4K Clean Air Companion

The Ion4K Clean Air Companion is a compact machine that electronically charges the air, removing harmful particles and odors from the environment by rapidly driving dust and other contaminants to the ground. This allows for a cleaner worksite, improving health and safety for on-site construction workers. It can be used during demolition and renovation projects, particularly on jobsites that require fast and extensive cleanups. The machine features a multispeed fan, locking caster wheels, and sturdy handles for easy transportation and maneuvering. Its simple control panel requires minimal input from the user, allowing more time to be spent on other tasks.

—National Flooring Equipment, www.nationalequipment.com

Bosch GAS20-17AH Wet/Dry Dust Extractor

Part of the Bosch PRO+GUARD™ system, the GAS20-17AH is an industrial-grade wet/dry dust extractor with a maximum 300 ft³ (8.5 m³) of air per minute capacity that filters fine dust, coarse dirt, and liquids. The GAS20-17AH has a 17 gal. (64.4 L) capacity and a 17.5 amp motor. Its HEPA filter captures 99.97% of particles at 0.3 microns and larger to help users move toward OSHA silica dust regulation compliance, and it self-cleans the HEPA filter through reverse airflow every 15 seconds. This dust extractor offers powerful performance for heavy-duty applications, including concrete cutting and surface grinding with larger 7 and 9 in. (178 and 229 mm) grinders and up to 12 in. (305 mm) cut-off tools. The unit has a dumping mechanism for emptying convenience, a discharge hose for easy drainage, and a water-level sensor to help preclude overfilling.

—Bosch, www.boschtools.com



Ultrite Coating Remover

Ultrite Coating Remover from W.R. MEADOWS is a soy gel that lifts a wide range of one-part topical coatings, such as sealers, acrylics, urethanes, latexes, lacquers, enamels, and some epoxies, from a variety of surfaces, including concrete, masonry, wood, and metal. Ultrite Coating Remover can remove multiple layers in one application without vigorous scrubbing. It does not contain methylene chloride, is low odor, and is safe for interior use. Available in 1 gal. (3.8 L) units, 5 gal. (18.9 L) pails, and 55 gal. (208 L) drums, this product can be used for warehouses, industrial plants, schools, automotive plants, parking garages, plazas, and service stations.

—W.R. MEADOWS, www.wrmeadows.com

ACI UNIVERSITY'S CERTIFICATE PROGRAMS:

Provide an in-depth course of study and the ability to earn a credential illustrating your commitment to expanding your knowledge. Courses include:

- Fundamentals of Concrete and Materials
- Anchorage Design
- Concrete Repair Application Procedures
- Fundamentals of Concrete Construction



aci UNIVERSITY

www.ACIUniversity.com

